



MODEL 2150 | Specification Sheet
Commercial Series • Low Voltage • Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1/8" DIA x 4 3/8" H

ORDERING INFORMATION

EXAMPLE: *HT-2150-CSN-4.5-W-36*

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT	2150			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT Hanging Downlight	2150	CSN Natural Copper	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	BL Flat Cool Blue Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb louver
			4.5-W-25 4.5 Watts Warm 25° Spot	
		SS Stainless Steel	4.5-W-36 4.5 Watts Warm 36° Flood	
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	
		5.5-W-15 5.5 Watts Warm 15° Narrow Spot		
		5.5-W-25 5.5 Watts Warm 25° Spot		
		5.5-W-36 5.5 Watts Warm 36° Flood		
		5.5-W-60 5.5 Watts Warm 60° Wide Flood		
		NL No Lamp		



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel fitted with machined solid brass base.

FINISH:

Brushed Natural Copper or Stainless Steel.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

LENS:

Clear, tempered glass lens.
Optical effect lenses are available

MOUNTING:

Solid brass loop with a six-foot stainless steel cable-hanger included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

