



MODEL 2500 | Specification Sheet
Commercial Series • Low Voltage • Bollard

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES

Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Aluminum
Dimensions	2 1/8" DIA x 16" H



ORDERING INFORMATION

EXAMPLE: **BR-2500-B-4.5-W-36**

MOUNTING	MODEL	FINISH	LED
BR	2500		

MOUNTING	MODEL	FINISH	LED	ORDERING NOTES
BR ABS Ground Stake	2500	B Black	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	Fixtures shipped with specified mounting hardware.
		Z Architectural Bronze	4.5-W-25 4.5 Watts Warm 25° Spot	
		DZ Dark Bronze	4.5-W-36 4.5 Watts Warm 36° Flood	
		GT Granite	4.5-W-60 4.5 Watts Warm 60° Wide Flood	
		W White	5.5-W-15 5.5 Watts Warm 15° Narrow Spot	
		BR Architectural Brick	5.5-W-25 5.5 Watts Warm 25° Spot	
		LZ Light Bronze	5.5-W-36 5.5 Watts Warm 36° Flood	
		SB Special Bronze	5.5-W-60 5.5 Watts Warm 60° Wide Flood	
		GG Glossy Gray	NL No Lamp	
		R Rust		
		HG Hunter Green		
		WB Weathered Bronze		
		WI Weathered Iron		
		GM Graphite Metallic		
		G Verde		
P Pewter				
M Mocha				
OF Olde Finish				



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

POST CONSTRUCTION:

Heavy-gauge extruded aluminum (1/8" wall thickness).

FINISH:

Powder coat finish for Aluminum Door Cover available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Clear, machined acrylic lens.

MOUNTING:

Aluminum mounting base with ABS ground stake included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

