



**PROFESSIONAL**  
OUTDOOR LIGHTING



## Photometric Test Summary - Vista 1045 Series

File No.	Catalog No.	Description	Test Voltage	Beam Angle (H/V)	Field Angle (H/ V)	Total Lumens	Wattage	Efficacy	CRI	CCT
L021703901	1045-X-VNS-C-MV-ND	LED Accent, VNS Distribution	120VAC	17.2/17.2	32.8/32.8	1409.26	25.76	54.71	84.9	3092
L021703902	1045-X-NS-C-MV-ND	LED Accent, NS Distribution	120VAC	17.5/17.5	38.6/38.6	2324.78	25.29	91.94	85.2	3119
L021703903	1045-X-MF-C-MV-ND	LED Accent, MF Distribution	120VAC	29.9/29.9	69.2/69.2	2230.34	25.86	86.26	85.3	3083
L021703904	1045-X-WF-C-MV-ND	LED Accent, WF Distribution	120VAC	50.6/47.6	78.6/76.2	2076.84	25.4	81.76	85.2	3059
*L021703905	1045-X-VNS-B-MV-ND	LED Accent, VNS Distribution	120VAC	17.2/17.2	32.8/32.8	1141.48	20.87	54.69	N.A.	N.A.
*L021703906	1045-X-VNS-A-MV-ND	LED Accent, VNS Distribution	120VAC	17.1/17.1	32.8/32.8	789.36	14.43	54.7	N.A.	N.A.
*L021703907	1045-X-NS-B-MV-ND	LED Accent, NS Distribution	120VAC	17.5/17.5	38.6/38.6	1883.28	20.48	91.96	N.A.	N.A.
*L021703908	1045-X-NS-A-MV-ND	LED Accent, NS Distribution	120VAC	17.5/17.5	38.6/38.6	1301.56	14.16	91.92	N.A.	N.A.
*L021703909	1045-X-MF-B-MV-ND	LED Accent, MF Distribution	120VAC	29.9/29.9	69.2/69.2	1807.18	20.95	86.26	N.A.	N.A.
*L021703910	1045-X-MF-A-MV-ND	LED Accent, MF Distribution	120VAC	29.9/29.9	69.2/69.2	1249.34	14.48	86.28	N.A.	N.A.
*L021703911	1045-X-WF-B-MV-ND	LED Accent, WF Distribution	120VAC	50.6/47.6	78.6/76.1	1682.2	20.57	81.78	N.A.	N.A.
*L021703912	1045-X-WF-A-MV-ND	LED Accent, WF Distribution	120VAC	50.3/47.6	78.4/76.2	1162.54	14.22	81.75	N.A.	N.A.

\*Indicates a representative photometric from Vista Model 1045 using the same optic, LED, and optic enclosure. Reports are pro-rated from highest drive current.

\*\*LED Flood report includes LM-79 Report, Report Summary, Axial Display, Isocandela Curve