



MODEL 2350 | Specification Sheet
Commercial Series • Low Voltage • Up / Accent / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Brass
Dimensions	2 1/2" DIA x 6 3/4" D

ORDERING INFORMATION

EXAMPLE: *GR-2350-BSN-4.5-W-36-FR*

CATEGORY	MODEL	FINISH	LED
	2350		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
GR ABS Ground Stake	2350	BSN Natural Brass	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	BL Flat Cool Blue Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb louver
WB Brass Wall-Mount Canopy			BSO Olde Brass	
			4.5-W-36 4.5 Watts Warm 36° Flood	
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	
			5.5-W-15 5.5 Watts Warm 15° Narrow Spot	
			5.5-W-25 5.5 Watts Warm 25° Spot	
			5.5-W-36 5.5 Watts Warm 36° Flood	
			5.5-W-60 5.5 Watts Warm 60° Wide Flood	
			NL No Lamp	



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Solid Brass.

FINISH:

Natural Brass or Olde Brass.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

MOUNTING:

Solid Brass knuckle with 1/2" NPS thread.

FASTENERS/INSERTS:

Fasteners are stainless steel and brass.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

