



**PROFESSIONAL
OUTDOOR LIGHTING**



Photometric Test Summary: Vista 1141 Series

File No.	Catalog Number	Description	Beam Angle (H°xV°)	NEMA TYPE	Max Candela	Max Candela Angle	Total Lumens	Wattage	Efficacy	CCT
L102110502	1141-NS-X-B-MV-ND	LED Linear Ingrade, NS Distribution	83° x 24°	7H x 5V	1352	-1H, 0V	1201	19.3	62	3144
L072112808R01	1141-MF-X-B-MV-ND	LED Linear Ingrade, MF Distribution	96° x 57°	7H x 5V	1378	0H, 9V	2029	18.8	108	3157
L072112809R01	1141-WF-X-B-MV-ND	LED Linear Ingrade, WF Distribution	81° x 92°	7H x 7V	719	0H, -19.5V	1604	19.0	84	3128
L072112807R01	1141-WG-X-B-MV-ND	LED Linear Ingrade, WG Distribution	97° x 23°	7H x 4V	2799	-3H, -7V	2103	19.0	111	3164
L072112806R01	1141-WW-X-B-MV-ND	LED Linear Ingrade, WW Distribution	81° x 44°	7H x 7V	1069	0H, -29V	1686	19.0	89	3143
L102110501	1141-NS-X-A-MV-ND	LED Linear Ingrade, NS Distribution	83° x 25°	7H x 5V	956	0H, 1V	875	13.4	64	3135
L092110508	1141-MF-X-A-MV-ND	LED Linear Ingrade, MF Distribution	91° x 52°	7H x 5V	1016	0H, 7V	1332	13.4	99	3155
L092110509	1141-WF-X-A-MV-ND	LED Linear Ingrade, WF Distribution	75° x 86°	7H x 7V	518	0H, -17V	1054	13.4	79	3133
L092110507	1141-WG-X-A-MV-ND	LED Linear Ingrade, WG Distribution	95° x 17°	7H x 4V	2102	0H, -5V	1286	13.4	96	3157
L092110506	1141-WW-X-A-MV-ND	LED Linear Ingrade, WW Distribution	77° x 43°	6H x 6V	787	0H, -25.5V	1132	13.4	84	3158

*LED Flood Report includes LM-79 Report, Report Summary, Axial Display, Isocandela.