



MODEL 2125 | Specification Sheet
Commercial Series • Low Voltage • Path & Area

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Copper or Brass
Dimensions	6" DIA x 13 ¼" H

ORDERING INFORMATION

EXAMPLE: **PR-2125-BSN-W-LB5ND**

MOUNTING	MODEL	FINISH	LED
PR	2125	BSN	

MOUNTING	MODEL	FINISH	LED
PR ABS Ground Stake	2125	CSN Natural Copper BSN Natural Brass BSO Olde Brass	W-LB2ND 2.5 Watts Warm Integrated LED
			N-LB2ND 2.5 Watts Neutral Integrated LED
			C-LB2ND 2.5 Watts Cool Integrated LED
			W-LB5ND 5 Watts Warm Integrated LED
			N-LB5ND 5 Watts Neutral Integrated LED
			C-LB5ND 5 Watts Cool Integrated LED
			150-W-G4 1.5 Watts Warm G4 LED Lamp
NL No Lamp			





SPECIFICATIONS

HOUSING CONSTRUCTION:

Solid Copper or Brass shade.
Twist-To-Lock Solid Brass lamp base.

STEM CONSTRUCTION:

1/2" Solid Copper or Brass pipe.

FINISH:

Brushed Natural Copper, Natural Brass or Olde Brass finish.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

LENS:

Textured, high-impact polycarbonate lens.

MOUNTING:

Bottom of stem threaded with 1/2" NPT.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

