



**PROFESSIONAL
OUTDOOR LIGHTING**



NVLAP
NVLAP LAB CODE 200927-0



Photometric Test Summary - Vista 1500 Series

File No.	Catalog Number	Description	Test Voltage	# of LEDs (Modules)	Report Type	IES Classification	BUG Rating	Total Lumens	Wattage	Efficacy	CRI	CCT
L061805901	1501-AL-3LED-W	Louvered Steplight-Horizontal	120VAC	3 Cree X-TE	Roadway	Type IV, Very Short	B0-U1-G1	116	6.23	18.63	81	3092
L061805902	1503-AL-6LED-W	Louvered Steplight-Horizontal	120VAC	6 Cree X-TE	Roadway	Type IV, Very Short	B0-U2-G1	233.1	11.15	20.91	81	3049
L061805903	1505-AL-9LED-W	Louvered Steplight-Horizontal	120VAC	9 Cree X-TE	Roadway	Type IV, Very Short	B0-U2-G1	378	17.28	21.88	81	3094
L061805904	1501-AB-3LED-W*	Border Steplight-Horizontal	120VAC	3 Cree X-TE	Roadway	Type III, Very Short	B0-U2-G1	210.2	6.1	34.45	81	3102
L061805905	1502-AB-3LED-W*	Border Steplight-Vertical	120VAC	3 Cree X-TE	Roadway	Type IV, Very Short	B0-U1-G1	272.6	6.48	42.07	81	3156
L061805906	1503-AB-6LED-W*	Border Steplight-Horizontal	120VAC	6 Cree X-TE	Roadway	Type IV, Very Short	B0-U2-G1	473.5	11.04	42.9	81	3075
L061805907	1504-AB-6LED-W*	Border Steplight-Vertical	120VAC	6 Cree X-TE	Roadway	Type IV, Very Short	B0-U2-G1	506.3	9.94	50.94	81	3082
L061805908	1505-AB-9LED-W*	Border Steplight-Horizontal	120VAC	9 Cree X-TE	Roadway	Type III, Very Short	B0-U3-G1	740.4	17.34	42.69	81	3098

LED LM-79 Flood Report includes Report Summary, LCS, Candela Tabulation, Coefficient of Utilization, Polar Graph, LCS Graph, Isofootcandle Lines of Horizontal Illumination

*1501-AB-3LED represents 1501-GB, 1501-BB, 1501-SB

*1502-AB-3LED represents 1502-GB, 1502-BB, 1502-SB, 1502-BL2, 1502-SL2

*1503-AB-6LED represents 1503-GB, 1503-BB, 1503-SB

*1504-AB-6LED represents 1504-GB, 1504-BB, 1504-SB, 1504-BL2, 1504-SL2

*1505-AB-9LED represents 1505-GB, 1505-BB, 1505-SB