

Type: \_\_\_\_\_  
 Model: \_\_\_\_\_  
 Project: \_\_\_\_\_

## SPECIFICATION SHEET

# MODEL: 1215 - 120V Series: Path & Spread Lights

### FIXTURE SPECIFICATIONS:

**LAMP TYPE:**

Candelabra base. 60W Maximum.  
 Lamp not included with fixture, order separately.  
 (See back page for LED lamp specifications)

**HOUSING:**

Die-cast, copper-free aluminum.

**STEM:**

1/4" schedule-40 aluminum pipe with 1/2" NPT custom bushing designed with a stress-dispersing collar, to provide strength and stability for mounting.

**FINISH:**

Polyester powder-coat finish available in Black, Verde, Architectural Brick, Architectural Bronze, Light Bronze, Dark Bronze, Granite, Pewter, Terra-cotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White.

**SOCKET/LAMP HOLDER:**

High temperature phenolic candelabra base socket.

**LENS:**

Clear, high-impact, polycarbonate lens.

**MOUNTING:**

Aluminum stem with 1/2" NPT on bottom and jam nut included. Fixture may be mounted into threaded hubs in junction boxes, ground stakes, or grade-mounted ballast enclosures.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**


Prewired with 200°C-rated wire along with a grounded lead.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for line voltage landscape luminaires (UL 1598). The maximum wattages allowed by Underwriters Laboratories (UL) for the U.S. and Canadian markets may vary. Maximum wattages specified are Underwriters Laboratories U.S. standard. Please contact Vista for any questions about the maximum wattages allowed by UL Canadian standards.

All Vista luminaires are **MADE IN THE U.S.A.**

### DIMENSIONS:



Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATION SHEET

### MODEL: 1215 - 120V Series: Path & Spread Lights

#### LED LAMP SPECIFICATIONS (if applicable):

**LAMP TYPE:**

High Output LED with Vista exclusive smart-driver, powered to operate for 50,000 hours.

**OPTICS:**

Integral high-efficiency optics available in spot through flood beam spreads.

**ELECTRICAL:**

Input voltage range 6–15V AC, regulated to achieve uniform illumination throughout the cable run of fixtures. Integral surge & reverse polarity protection.

#### FIXTURE ORDERING INFORMATION

**TO ORDER FIXTURE:** Select appropriate choice from each column as in the following example

EXAMPLE: 1215-B-CR

MODEL	FINISH	LENS
1215	<b>B</b> - Black <b>G</b> - Verde <b>BR</b> - Architectural Brick <b>Z</b> - Architectural Bronze <b>LZ</b> - Light Bronze <b>DZ</b> - Dark Bronze <b>GT</b> - Granite <b>P</b> - Pewter <b>TC</b> - Terra-cotta <b>R</b> - Rust <b>HG</b> - Hunter Green <b>M</b> - Mocha <b>WB</b> - Weathered Bronze <b>WI</b> - Weathered Iron <b>W</b> - White	<b>CR</b> - Clear lens

Lamp not included with fixture, order separately. For available lamps, see Lamp Guide, Vista catalog.

*Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.*