

TYPE:	MODEL:
PROJECT:	

PRODUCT FEATURES





Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	3" H x 3¾" W x 2¼" D



ORDERING INFORMATION

EXAMPLE: **SL-4250-B-W-LB5ND**

CATEGORY MODEL FINISH LED
SL 4250

CATEGORY	MODEL	FINISH		LED	
SL Step Light	4250	В	Black	W-LB2ND	2.5 Watts Warm Integrated LED
		z	Architectural Bronze	N-LB2ND	2.5 Watts Neutral Integrated LED
		DZ	Dark Bronze	C-LB2ND	2.5 Watts Cool Integrated LED
		GT	Granite	W-LB5ND	5 Watts Warm Integrated LED
		w	White	N-LB5ND	5 Watts Neutral Integrated LED
		BR	Architectural Brick	C-LB5ND	5 Watts Cool Integrated LED
		LZ	Light Bronze	1.1-W-GS-T3	1.1 Watts Warm T3 LED Lamp
		SB	Special Bronze		
		GG	Glossy Gray	NL	No Lamp
		R	Rust		
		HG	Hunter Green		
		WB	Weathered Bronze		
		wı	Weathered Iron		
		GM	Graphite Metallic		
		G	Verde		
		P	Pewter		
		м	Mocha		
		OF	Olde Finish		



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FINISH:

Powder coat finish for Aluminum Door Cover available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Frosted, tempered glass lens.

MOUNTING:

Surface mounting plate included. No recessed box required.

FASTENERS:

All fasteners are stainless steel.

LED:

- Integrated LED Module. 2.5 5 Watts.
- T3 LED Lamp. 1.1 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

WIRING:

Provided with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

DIMENSIONS







