

5274



Composite with Stainless Steel or Brass

50 W max (halogen)

MR-16 Lamp or LED

LN-20 BAB/FG Std

5275



Composite with Stainless Steel or Brass

50 W max (halogen)

MR-16 Lamp or LED

LN-20 BAB/FG Std

5276



Composite with Stainless Steel or Brass

50 W max (halogen)

MR-16 Lamp or LED

LN-20 BAB/FG Std

5284



Composite with Stainless Steel or Brass

50 W max (halogen)

MR-16 Lamp or LED

LN-20 BAB/FG Std

5285



Composite with Stainless Steel or Brass

50 W max (halogen)

MR-16 Lamp or LED

LN-20 BAB/FG Std

5286









Composite with Stainless Steel or Brass

50 W max (halogen)

MR-16 Lamp or LED

LN-20 BAB/FG Std



<b>HOUSING</b>	<ul style="list-style-type: none"> <li>» Injection-molded, reinforced polymer</li> <li>» Formulated for most Vista polyester powder-coated finishes</li> <li>» Exceptional strength and UV stability</li> <li>» 5284, 5285, 5286: Suspended in 6" ABS well</li> </ul>
<b>LENS COVER</b>	<ul style="list-style-type: none"> <li>» Solid Brass or Solid Stainless Steel</li> <li>» CNC Machined</li> <li>» Solid Brass available with an Olde Brass finish</li> <li>» Silicone O-ring gasket</li> <li>» Superior weather-tight seal</li> </ul>
<b>FINISH</b>	<ul style="list-style-type: none"> <li>» Lens cover available in Natural Brass, Olde Brass, or Stainless Steel</li> </ul>
<b>SOCKET/LAMP HOLDER</b>	<ul style="list-style-type: none"> <li>» Proprietary ceramic socket</li> <li>» Nickel contacts</li> <li>» Stainless steel springs</li> <li>» Teflon-jacketed wire leads</li> </ul>
<b>LENS</b>	<ul style="list-style-type: none"> <li>» Convex</li> <li>» Clear</li> <li>» Tempered</li> <li>» Shock- and heat-resistant</li> <li>» Soda-lime glass</li> <li>» For optical effect lenses, see ordering information.</li> </ul>

<b>OPTICS/AIMING</b>	<ul style="list-style-type: none"> <li>» Adjustable and lockable lamp bracket</li> <li>» ±25° of tilt</li> <li>» 360° rotation of housing</li> <li>» 5284, 5285, 5286: ±45° of tilt with housing bracket</li> </ul>
<b>LAMP TYPE</b>	<ul style="list-style-type: none"> <li>» Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.</li> </ul>
<b>PHOTOMETRICS</b>	<ul style="list-style-type: none"> <li>» For photometric data, see pages 131-149.</li> </ul>
<b>MOUNTING</b>	<ul style="list-style-type: none"> <li>» In-grade</li> <li>» Conduit mount option has two 3/4" NPT inlets</li> <li>» Optional concrete mounting kit available, see page 127.</li> </ul>
<b>FASTENERS</b>	<ul style="list-style-type: none"> <li>» Stainless steel fasteners</li> </ul>
<b>WIRING</b>	<ul style="list-style-type: none"> <li>» Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.</li> </ul>

LED SPECIFICATIONS  Look for this mark on products where LED options are available.	
LED Lamp	Integrated LED
High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.	High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

ORDERING INFORMATION <i>Select appropriate choice from each column</i>					<b>example: GW-5271-B-BAB/FG-CBL</b>
Mounting	No.	Lens Cover	Lamp	Lenses/Accessories	
GW In-grade	5274	BSN Solid Brass trim	LAMP See reference codes, pages 128-130	CBL Convex Cool-Blue Lens	HL Honeycomb Louver JBCP-150 Concrete Mounting Kit*
CM In-grade conduit mount	5275	BSO Solid Brass trim w/Olde Brass finish		CFR Convex Frosted Lens	
	5276	SS Stainless Steel trim		SL Flat Spread Lens	
			INTEGRATED LED See reference codes, page 130, group F	DBL Flat Dark Blue Lens	
				GL Flat Dark Green Lens	
				RL Flat Red Lens	
				YL Flat Amber Lens	

**NOTE:** not all accessories are available for all fixtures. See footnotes below before ordering.  
 \* Only available for models 5274, 5275, 5276.  
 Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.