

MODEL:
,
_

PRODUCT FEATURES

Wattage	300 – 1200 W
Secondary Voltage	11 – 15 VAC
Housing	Stainless Steel
Dimensions	17" H x 9" W x 5½" D



ORDERING INFORMATION

EXAMPLE: **MT-600DT**

SERIES MODEL OPTIONAL FINISH MT

SERIES	MODEL		MODEL OPTIONAL FINISH		IONAL FINISH	ORDERING NOTES			
MT Multi-Tap Transformer	Transformer 300	300 Watts		Clear powder coat finish standard		See the following for accessory			
	300T	300 Watts T timer *	В	Black			descriptions:		
	300DT	300 Watts DT timer *	z	Architectural Bronze	т	т	т	т	Removable multi-setting mechanical
	300DA	300 Watts DA timer *	DZ	Dark Bronze		24-hour timer			
	300RP	300 Watts RP photocell *	GT	Granite	DT Remov 7-day t	DT	Removable multi-setting digital		
	600	600 Watts (300 W x 2)	w	White		7-day timer			
	600T	600 Watts (300 W x 2) T timer *	BR	Architectural Brick	DA	Removable multi-setting digital astronomical timer			
	600DT	600 Watts (300 W x 2) \mid DT timer *	LZ	Light Bronze		astronomical timer			
	600DA	600 Watts (300 W x 2) \mid DA timer *	SB	Special Bronze	RP	P Remote wired photocell with electronic timer			
	600RP	600 Watts (300 W x 2) RP photocell *	GG	Glossy Gray					
	900	900 Watts (300 W x 3)	R	Rust		Accessories not required for operation of transformer			
	900T	900 Watts (300 W x 3) \mid T timer *	HG	Hunter Green					
	900DT	900 Watts (300 W x 3) \mid DT timer *	WB	Weathered Bronze					
	900RP	900 Watts (300 W x 3) \mid RP photocell *	wı	Weathered Iron					
	1200	1200 Watts (300 W x 4)	GM	Graphite Metallic					
	1200T	1200 Watts (300 W x 4) \mid T timer *	G	Verde					
	1200DT	1200 Watts (300 W x 4) \mid DT timer *	P	Pewter					
	1200RP	1200 Watts (300 W x 4) RP photocell *	м	Mocha					
			OF	Olde Finish					



SPECIFICATIONS

HOUSING CONSTRUCTION:

20-gauge 304 stainless steel.

 $\frac{1}{2}$ " – $\frac{3}{4}$ " knockouts on each side of enclosure for conduit and accessory mounting as well as a removable, swing-down enclosure bottom with Adjustable Cable Raceway Feeder and multiple $\frac{1}{2}$ " – $\frac{3}{4}$ " and 2" knockouts.

NEMA ENCLOSURE RATING:

ЗK

FINISH:

Clear powder coat finish standard. Also available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

TERMINALS:

- Low voltage terminal strip for multiple cable connections
- 120-volt terminal strip for easy hard-wiring and an accessory terminal strip

PRIMARY PROTECTION:

Auto thermal shut-off

SECONDARY PROTECTION:

Resettable high performance magnetic circuit breaker. Fully grounded and isolated with encapsulated core and coil.

WIRING

6-foot, heavy-gauge, grounded, water-resistant power cord with integrally molded plug.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

Pool & Spa Ready - Suitable for Use with Submersible Luminaires (power cord must be shortened to a 3-foot maximum length - see Installation Instructions).

AVAILABLE POWER RATING:

300, 600, 900 or 1200 Watts

PRIMARY VOLTAGE:

120 Volts

(Also available in 208V, 230V or 277V, 50 or 60 cycle - Special order only.)

SECONDARY VOLTAGE:

11, 12, 13, 14 and 15 Volts

DIMENSIONS







