

TYPE:	MODEL:
PROJECT:	

PRODUCT FEATURES

Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Туре	MR-16 LED
Housing	Die-cast Aluminum
Dimensions	2¼" DIA x 6¾" D



EXAMPLE: **DL-2236-B-4.5-W-36-FR**

ORDERING INFORMATION

CATEGORY MODEL FINISH LED ACCESSORIES
DL 2236

CATEGORY	MODEL	FINISH		LED		ACCESSORIES	
DL Wall-Mount Long Shroud	2236	В	Black	4.5-W-15	4.5 Watts Warm 15° Narrow Spot	FR	Frosted Lens
		z	Architectural Bronze	4.5-W-25	4.5 Watts Warm 25° Spot	BL	Flat Cool Blue Lens
		DZ	Dark Bronze	4.5-W-36	4.5 Watts Warm 36° Flood	SL	Flat Spread Lens
		GТ	Granite	4.5-W-60	4.5 Watts Warm 60° Wide Flood	DBL	Flat Dark Blue Lens
		w	White	5.5-W-15	5.5 Watts Warm 15° Narrow Spot	GL	Flat Dark Green Lens
		BR	Architectural Brick	5.5-W-25	5.5 Watts Warm 25° Spot	RL	Flat Red Lens
		LZ	Light Bronze	5.5-W-36	5.5 Watts Warm 36° Flood	YL	Flat Amber Lens
		SB	Special Bronze	5.5-W-60	5.5 Watts Warm 60° Wide Flood	HL	Honeycomb louver
		GG	Glossy Gray	NL	No Lamp		
		R	Rust				
		HG	Hunter Green				
		WB	Weathered Bronze				
		wı	Weathered Iron				
		GМ	Graphite Metallic				
		G	Verde				
		P	Pewter				
		М	Mocha				
		OF	Olde Finish				



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Clear, tempered glass lens. Optical effect lenses are available.

MOUNTING:

Adjustable bracket included.

FASTENERS/INSERTS:

All fasteners are stainless steel.

LED:

MR-16 LED Lamp. 295 or 389 Lumens. 4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

WIRING:

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°) Narrow Spot **25** (25°) Medium Flood **36** (36°) Wide Flood **60** (60°)



