

TYPE:	MODEL:
PROJECT:	

Р	RC	DC	U	C	ΓF	E/	٩Т	U	R	ES

PROJECT:	
r ROJECI.	

Wattage	9 W
Voltage	11 – 18 VAC
Lumens	110 – 615 Lumens
Distribution	38° (MF)
ССТ	2200 K – 5700 K CCT White
CRI	80 CRI min.
Wireless Control	VistaPro Smart App with Bluetooth Mesh Technology
Housing	Die-cast Aluminum
Dimensions	3" DIA x 6 5/16" D

chroma connect

Bluetooth MESH

ORDERING INFORMATION

EXAMPLE: GR-3105-B-9-RGBW-38-HL

MOUNTING	MODEL	FINISH	WATTAGE	COLOR	DISTRIBUTION	ACCESSORIES
	3105		9	RGBW	38	

MOUNTING	MODEL	FINISH		
GR ABS ground stake WR Wall-mount canopy TR Tree-mount junction box	3105	B Black Z Architectural Bronze DZ Dark Bronze GT Granite W White	BR Architectural Brick LZ Light Bronze SB Special Bronze GG Glossy Gray R Rust HG Hunter Green WB Weathered Bronze WI Weathered Iron GM Graphite Metallic	G Verde P Pewter M Mocha OF Olde Finish
WATTAGE	COLOR	DISTRIBUTION	ACCESSORIES	ORDERING NOTES
9 9 Watts	RGBW RGB Color Options + Tunable White	38 38° Flood	BD Barn Doors FS Full Light Shield HS Half Light Shield HL Honeycomb Louver 5 5' Wire Lead	Fixtures shipped with specified mounting hardware. If fixture is to be used in conjunction with Extended Arm Mount (EAM): Must specify with extended wire length





SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum. Optic and driver compartment environmentally sealed.

DOOR CONSTRUCTION:

Die-cast A360 aluminum.

Door is designed to shed water from the lens surface.

FINISH

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish. Custom Powder coat finishes available on request.

LENS

Tempered and beveled clear glass.

WATTAGE:

9 Watts.

INPUT VOLTAGE:

11 - 18 VAC / 60 Hz.

COLOR:

RGBW

COLOR TEMPERATURE:

2200 K - 5700 K CCT White.

LUMINOSITY:

110 lm – 615 lm.

REFLECTOR:

Precision molded metalized optics combined with glare controlling filters.

FASTENERS:

All fasteners are stainless steel.

WIRING

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

MOUNTING:

Injection-molded composite knuckle with $\frac{1}{2}$ " NPS thread.

COLOR RENDERING INDEX (CRI):

80

MINIMUM RATED LIFE:

40,000 Hrs.

BEAM SPREAD:

38°

DIMMING:

Yes

WIRELESS CONTROL:

VistaPro Smart App with Bluetooth Mesh Technology. Android and iOS compatible.

DIMENSIONS





