

TYPE:	MODEL:
PROJECT:	

PRODUCT FEATURES





Wattage	1 – 5 W
Voltage	9 – 15 VAC
Faceplate	Brass, Copper or Stainless Steel
Dimensions	4¾" L x 2½" H x 3½" D

ORDERING INFORMATION

EXAMPLE: **SL-2141-BSN-W-LB5ND**

CATEGORY	MODEL	FINISH	LED
SL Step Light	2141	BSN Natural Brass	W-LB2ND 2.5 Watts Warm Integrated LED
		BSO Olde Brass	N-LB2ND 2.5 Watts Neutral Integrated LED
		CSN Natural Copper	C-LB2ND 2.5 Watts Cool Integrated LED
		SS Stainless Steel	W-LB5ND 5 Watts Warm Integrated LED
			N-LB5ND 5 Watts Neutral Integrated LED
			C-LB5ND 5 Watts Cool Integrated LED
			150-W-G4 1.5 Watts Warm G4 LED Lamp
			NL No Lamp



SPECIFICATIONS

HOUSING CONSTRUCTION:

Stamped & formed aluminum recessed box with $\frac{1}{2}$ " knockouts on the back & side.

COVER PLATE CONSTRUCTION:

Stamped solid brass, copper, or stainless steel.

LENS:

Translucent, high-impact polycarbonate lens.

MOUNTING:

Recessed mounting box included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 2.5 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

DIMENSIONS







