

TYPE:	MODEL:
PROJECT:	, ,

PRODUCT FEATURES





Wattage	5 W
Voltage	9 – 15 VAC
Shroud	Brass, Copper or Stainless Steel
Dimensions	12 ¼" L x 1 ¼" H x 6" D

ORDERING INFORMATION

EXAMPLE: **SL-4261M-B-W-LB2ND**

CATEGORY	MODEL	FINISH				LED		
SL Step Light	4261M	В	Black	R	Rust	W-LB2ND	2.5 Watts (x2) Warm Integrated LED	
		z	Architectural Bronze	HG	Hunter Green	C-LB2ND	2.5 Watts (x2) Cool Integrated LED	
		DZ	Dark Bronze	WB	Weathered Bronze			
		GT	Granite	WI	Weathered Iron			
		w	White	GM	Graphite Metallic			
		BR	Architectural Brick	G	Verde			
		LZ	Light Bronze	P	Pewter			
		SB	Special Bronze	М	Mocha			
		GG	Glossy Gray	OF	Olde Finish			
		BSN	Natural Brass	CSN	Natural Copper			
		вѕо	Olde Brass	SS	Stainless Steel			



SPECIFICATIONS

SHROUD CONSTRUCTION:

Brass, Copper or Stainless Steel.

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FINISH:

Available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Textured, high-impact polycarbonate lens.

FASTENERS:

All fasteners are stainless steel.

LED:

Integrated LED Module. 5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

WIRING:

Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

CERTIFICATION

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

DIMENSIONS





