

TYPE:	MODEL:
PROJECT:	

PRODUCT FEATURES





Material	Aluminum
Adjustment	Automatic Expansion
Dimensions	3" H x [24" 27" 30"] DIA



ORDERING INFORMATION

EXAMPLE: TRM-3-B-MA-27-B12-ND

MODEL	JUNCTION BOX	FINISH	ADJUSTMENT	DIAMETER	HUB ENTRY	INPUT / DIM
TRM			MA		B12	

MODEL	JUNCTION BOX QTY	FINISH		
TRM	3 Three boxes 120° apart	B Black	BR Architectural Brick	G Verde
	4 Four boxes 90° apart	Z Architectural Bronze	LZ Light Bronze	P Pewter
		DZ Dark Bronze	SB Special Bronze	M Mocha
		GT Granite	GG Glossy Gray	OF Olde Finish
		W White	R Rust	
			HG Hunter Green	
			WB Weathered Bronze	
			WI Weathered Iron	
			GM Graphite Metallic	
ADJUSTMENT	TREE RING DIAMETER	ELECTRICAL HUB ENTRY	INPUT / DIMMING	ORDERING NOTES
MA Manual Adjustment	24 24 inch Tree Diameter Range: [3] 12"-16", [4] 13"-15"	B12 NPT ½" – 14 bottom *	LV 2 Conductor cabling (Low Voltage)	* Only one junction box will have a bottom hub entry
	27 1nch Tree Diameter Range: [3] 14"–18", [4] 16"–18"		ND 3 Conductor cabling (Line Voltage)	Automatic Adjustment option available.
	30 30 inch Tree Diameter Range: [3] 18"–22", [4] 19"–21"		010 5 Conductor cabling (Line Voltage)	See TRM – AE specification.





SPECIFICATIONS

DESCRIPTION:

Tree Ring Mount accommodates tree ring diameters from 12" to 22", and the mounting of up to four flood lights. It is suitable for wet locations.

JUNCTION BOX CONSTRUCTION:

Die-cast A360 aluminum. Door is stamped 5052-H32 aluminum.

STRAP CONSTRUCTION:

1/6" thick x 3" wide affixed to each Junction Box with stainless steel fasteners. Strap is hinged and held with two 1/2" diameter stainless steel bolts. Hinge bolts are retained with stainless steel/nylon locking hex nuts. Hinged strap allows for easy installation around trees.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish. Custom Powder coat finishes available on request.

ELECTRICAL SUPPLY:

One NPT $\frac{1}{2}$ -14 bottom hub opening available for connection of flexible, outdoor rated conduit.

WIRING:

- 18/3 SEOOW outdoor rated waterproof cable [for Non-dimmable and Phase Cut (TRIAC/ELV-120VAC only) options]
- 18/5 SJTOW outdoor rated waterproof cable [for 0-10V dimming option]

TREE CLAMPING:

Tree clamp can be manually adjusted as the tree diameter grows without removing the tree ring. This adjustment feature uses %" stainless steel threaded rod with a 1 %" diameter machined clamp foot to affix to the tree. The clamp foot is designed to securely affix the Tree Ring Mount to the tree with minimum damage to the bark.

LOAD RATING:


- TRM-3: Maximum load of 6 pounds per junction box.
- TRM-4: Maximum load of 5.5 pounds per junction box.

Tested to UL 1598/CSA C22 No. 250.0 Standard.


CERTIFICATION:

cULus wet location listed.

JUNCTION BOX VARIATIONS



TRM-3 Manual Adjustment




TRM-4 Manual Adjustment







THREE BOX MA DIMENSIONS





24"






27"







30"




FOUR BOX MA DIMENSIONS





24"





27"





30"

