



**PROFESSIONAL
OUTDOOR LIGHTING**



Photometric Test Summary - Vista 1043 Series

File No.	Catalog No.	Description	Test Voltage	Beam Angle (H/V)	Field Angle (H/ V)	Total Lumens	Wattage	Efficacy	CRI	CCT
L021606505	1043-X-NS-30-F-MV-ND	LED Accent, NS Distribution	120VAC	18.9 / 18.9	45.0 / 45.0	1212.12	19.11	63.43	81.6	3028
L021606506	1043-X-MF-30-F-MV-ND	LED Accent, MF Distribution	120VAC	29.0 / 29.0	68.0 / 68.0	1188.4	19.73	60.24	82.1	3060
L091502202	1043-X-WF-30-F-MV-ND	LED Accent, WF Distribution	120VAC	45.2 / 45.2	77.3 / 77.3	1051.7	18.97	55.45	80.6	3081
L021606502	1043-X-NS-30-E-MV-ND	LED Accent, NS Distribution	120VAC	19.4 / 19.4	49.1 / 49.1	1034.72	15.62	66.23	81.6	2959
L021606503	1043-X-MF-30-E-MV-ND	LED Accent, MF Distribution	120VAC	28.6 / 28.6	67.5 / 67.5	1035.16	15.6	66.36	82.2	3039
L091502201	1043-X-WF-30-E-MV-ND	LED Accent, WF Distribution	120VAC	44.0 / 44.0	76.4 / 76.4	957.14	15.28	62.66	80.9	3044
L051503002*	1043-X-NS-30-D-MV-ND	LED Accent, NS Distribution	120VAC	18.6 / 18.6	40.2 / 40.2	737.82	10.01	73.69	82.7	3018
L051503003*	1043-X-MF-30-D-MV-ND	LED Accent, MF Distribution	120VAC	29.7 / 29.7	69.9 / 69.9	711.34	9.7	73.35	83.1	3037
L051506101	1043-X-WF-30-D-MV-ND	LED Accent, WF Distribution	120VAC	44.6 / 44.6	78.9 / 78.9	686.58	11.43	60.1	83	3033
L051503006*	1043-X-NS-30-C-MV-ND	LED Accent, NS Distribution	120VAC	14.3 / 14.3	30.5 / 30.5	566.04	7.42	76.25	81.5	3050
L051503007*	1043-X-MF-30-C-MV-ND	LED Accent, MF Distribution	120VAC	30.9 / 30.9	71.1 / 71.1	487.16	7.44	65.44	81.7	3051
L051503008*	1043-X-WF-30-C-MV-ND	LED Accent, WF Distribution	120VAC	43.7 / 43.7	75.9 / 75.9	542.24	7.64	70.94	81.6	3043
L051503010*	1043-X-NS-30-B-MV-ND	LED Accent, NS Distribution	120VAC	15.9 / 15.9	44.6 / 44.6	363.76	4.08	89.2	82.2	3050
L051503011*	1043-X-MF-30-B-MV-ND	LED Accent, MF Distribution	120VAC	31.9 / 31.9	71.3 / 71.3	320.58	4.06	78.88	83.6	3046
L051503012*	1043-X-WF-30-B-MV-ND	LED Accent, WF Distribution	120VAC	44.8 / 44.8	76.7 / 76.7	331.82	4.09	81.14	83.3	3023
L021606501	1043-X-VNS-30-B-MV-ND	LED Accent, VNS Distribution	120VAC	17.4 / 17.4	34.1 / 34.1	360.64	15.58	23.14	81.9	2970
L051503009*	1043-X-VNS-30-A-MV-ND	LED Accent, VNS Distribution	120VAC	15.7 / 15.7	30.6 / 30.6	134.98	4.06	33.27	83.8	3068

*Indicates a representative photometric from Vista Model 3105 using the same optic, LED, driver current, and optic enclosure.

**LED Flood report includes LM-79 Report, Report Summary, Axial Display, Isocandela