

| TYPE: | MODEL: |
|-------|--------|
| | |
| | |

PRODUCT DESCRIPTION

| 10" Full Bandpass Subwoofer | Qty 1 |
|--|-------|
| 4" Two-Way w/ 0.75" PEI Marine Grade Loudspeaker | Qty 4 |
| VSSL A.1 Home Amplifier | Qty 1 |
| Weatherproof Amplifier Enclosure | Qty 1 |
| Audio Interconnect Cable with ¼" TRS connectors | Qty 4 |
| 2-Way Audio cable splitters with ¼" TRS connectors | Qty 2 |
| Waterproof Marine Grade Demo Case with Handle and Wheels | Qty 1 |





SUBWOOFER FEATURES

| Туре | Full Bandpass Subwoofer |
|--------------------|--|
| Woofer | 10" Waterproof Cone with Rubber Surround |
| Frequency Response | 40-85Hz ± 3 dB |
| RMS Power Rating | @ 8Ω: 200 W |
| Magnet | 33 oz. Ferrite Magnet |
| SPL | 90dB @ 1W/1M |
| Power Handling | 150W |
| Bass Chamber | PVC |
| Port | Tuned Port with Flexible Rubber Elbow |
| Top Hat | Acrylonitrile Styrene Acrylate (ASA) |
| Weight | 26 lbs. |
| Dimensions | 12.7" D × 16.7" L |







SATELLITE SPEAKER FEATURES

| Туре | 2-Way Loudspeaker |
|--------------------|--|
| Woofer | 4" PP Waterproof Cone with Rubber Surround |
| Tweeter | 0.75" Marine Grade PEI Dome |
| Frequency Response | 80Hz–20kHz |
| SPL | 87 dB @ 1w/1m |
| Power Handling | 100W |
| Housing | Acrylonitrile Styrene Acrylate (ASA) |
| Weight | 2.66 lbs. |
| Dimensions | 5" D × 7.6" L × 7.7" H |



AMPLIFIER FEATURES

| Туре | VSSL A.1 Home Amplifier |
|--------------------|--|
| Output power | 35 watts @ 8 Ω RMS, 50 watts @ 4 Ω RMS |
| Frequency Response | 20Hz-20kHz |
| Channels | 2 |
| EQ | 7-band adjustable |
| S/N Ratio | >98dB A-weighted |
| Bluetooth | v4.2, EDR |
| WiFi | 2.4/5.8 GHz Dual Antenna MIMO |
| Wireless Inputs | Airplay2, Chromecast built-in, Spotify Connect, Alexa Cast, Bluetooth |
| Wired Inputs | Analog, Optical, Digital Coax, IR, Network |
| Wired Outputs | Analog, Optical, Digital Coax, Subwoofer, Network |
| Voice Controls | Google Assistant and Siri |
| Dimensions | 7.44" W × 1.69" H × 8.69" D |







AMPLIFIER ENCLOSURE FEATURES

| Туре | Weatherproof Amplifier Enclosure |
|-------------------|--|
| Housing | ABS + Polycarbonate |
| Protection Rating | NEMA 3R, 3RX/IP24 rated |
| Ventilation | Dual 3" vents with Thermostat controlled cooling fan and rain shields |
| Latch | Dual door latches with tamper-proof locking screw |
| Signal access | RF transparent enclosure |
| Wiring | Pre-wired with 120VAC outlets and 5 ft. power cord |
| Dimensions | 16.5" H × 13.7" W × 6.7" D |



