

TYPE:	MODEL:
PROJECT:	

## **PRODUCT FEATURES**





Wattage	1.5 W
Voltage	9 – 15 VAC
Lamp Туре	G4 LED
Housing	Aluminum
Dimensions	9" DIA x 12" H



# **ORDERING INFORMATION**

EXAMPLE: PR-8203-B-150-W-G4-RS

MOUNTINGMODELFINISHLEDACCESSORIESBR8203

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
BR Mounting Base with ABS ground stake 8203	<b>B</b> Black	<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp	RS 180° Reflector Shield	
		<b>Z</b> Architectural Bronze	<b>NL</b> No Lamp	
		<b>DZ</b> Dark Bronze		
		<b>GT</b> Granite		
		<b>W</b> White		
		BR Architectural Brick		
		<b>LZ</b> Light Bronze		
		SB Special Bronze		
		<b>GG</b> Glossy Gray		
		<b>R</b> Rust		
		<b>HG</b> Hunter Green		
		<b>WB</b> Weathered Bronze		
		<b>WI</b> Weathered Iron		
	GM Graphite Metallic			
	<b>G</b> Verde			
	<b>P</b> Pewter			
		<b>M</b> Mocha		
		<b>OF</b> Olde Finish		



## **SPECIFICATIONS**

## **HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

### POST CONSTRUCTION:

Extruded Aluminum (1/8" wall thickness).

#### **FINISH**

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish

### LENS:

Frosted, high-impact polycarbonate lens.

### MOUNTING:

Aluminum mounting base with ABS ground stake included.

## LED:

G4 LED Lamp. 1.5 Watts.

## **ELECTRICAL:**

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

## **FASTENERS:**

All fasteners are stainless steel.

#### WIRING

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

#### **CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

# **DIMENSIONS**





