

TYPE:	MODEL:

PRODUCT FEATURES





Wattage	2.5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	6" L x ¾" H x 3¼" D



ORDERING INFORMATION

EXAMPLE: **SL-4270-B-W-LB2ND**

CATEGORY MODEL FINISH LED

SL 4270

CATEGORY	MODEL	FINIS	IISH LED		
SL Step Light	4270	В	Black	W-LB2ND	2.5 Watts Warm Integrated LED
		z	Architectural Bronze	C-LB2ND	2.5 Watts Cool Integrated LED
		DZ	Dark Bronze		
		GT	Granite		
		w	White		
		BR	Architectural Brick		
		LZ	Light Bronze		
		SB	Special Bronze		
		GG	Glossy Gray		
		R	Rust		
		HG	Hunter Green		
		WB	Weathered Bronze		
		wı	Weathered Iron		
		GM	Graphite Metallic		
		G	Verde		
		P	Pewter		
		м	Mocha		
		OF	Olde Finish		



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FLANGE CONSTRUCTION:

Stainless Steel.

FINISH:

Available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS

Textured, high-impact polycarbonate lens.

FASTENERS:

All fasteners are stainless steel.

LED:

Integrated LED Module. 2.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

WIRING:

Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

DIMENSIONS





