



# MODEL 2165 | Specification Sheet

Commercial Series • Low Voltage • Path & Area

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES



|            |                    |
|------------|--------------------|
| Wattage    | 1 – 5 W            |
| Voltage    | 9 – 15 VAC         |
| Housing    | Copper or Brass    |
| Dimensions | 3 ½" DIA x 16 ½" H |

## ORDERING INFORMATION

EXAMPLE: **PR-2165-BSN-W-LB5ND**

| MOUNTING | MODEL | FINISH | LED |
|----------|-------|--------|-----|
| PR       | 2165  |        |     |

| MOUNTING            | MODEL | FINISH   | LED  |
|---------------------|-------|--|--|
| PR ABS Ground Stake | 2165  | CSN Natural Copper   | W-LB2ND 2.5 Watts   Warm   Integrated LED    |
|                     |       | CSO Olde Copper  | N-LB2ND 2.5 Watts   Neutral   Integrated LED |
|                     |       | BSN Natural Brass  | C-LB2ND 2.5 Watts   Cool   Integrated LED    |
|                     |       | BSO Olde Brass   | W-LB5ND 5 Watts   Warm   Integrated LED      |
|                     |       |  | N-LB5ND 5 Watts   Neutral   Integrated LED   |
|                     |       |  | C-LB5ND 5 Watts   Cool   Integrated LED      |
|                     |       |  | 150-W-G4 1.5 Watts   Warm   G4 LED Lamp      |
|                     |       | Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes. | NL No Lamp                                   |



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)  
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Solid Copper or Brass shade.  
Twist-To-Lock Solid Brass lamp base.

### STEM CONSTRUCTION:

½" Solid Copper or Brass pipe.

### FINISH:

Brushed Natural Copper, Natural Brass, Olde Copper finish or Olde Brass finish.  
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

Lens Cover also available in powder coat finish with the following standard colors:  
Black **(B)**, Architectural Bronze **(Z)**, Dark Bronze **(DZ)**, Granite **(GT)**, White **(W)**,  
Architectural Brick **(BR)**, Light Bronze **(LZ)**, Special Bronze **(SB)**, Glossy Gray **(GG)**,  
Rust **(R)**, Hunter Green **(HG)**, Weathered Bronze **(WB)**, Weathered Iron **(WI)**,  
Graphite Metallic **(GM)**, Verde **(G)**, Pewter **(P)**, Mocha **(M)** and Olde Finish **(OF)**.

### LENS:

Textured, high-impact polycarbonate lens.

### MOUNTING:

Bottom of stem threaded with ½" NPT.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | **(UL 1838)**
- Buy American Act **(BAA)**
- Build America, Buy America Act **(BABA)**

### LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

