



MODEL 5217 | Specification Sheet
Commercial Series • Low Voltage • Underwater

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	5" DIA x 5" D



ORDERING INFORMATION

EXAMPLE: **UW-5217-B-4.5-W-36-CFR**

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW	5217	B		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW Underwater	5217	B Black	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	CFR Crowned Frosted Lens
			4.5-W-25 4.5 Watts Warm 25° Spot	CBL Crowned Cool Blue Lens
			4.5-W-36 4.5 Watts Warm 36° Flood	SL Flat Spread Lens
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	DBL Flat Dark Blue Lens
			5.5-W-15 5.5 Watts Warm 15° Narrow Spot	GL Flat Dark Green Lens
			5.5-W-25 5.5 Watts Warm 25° Spot	RL Flat Red Lens
			5.5-W-36 5.5 Watts Warm 36° Flood	YL Flat Amber Lens
			5.5-W-60 5.5 Watts Warm 60° Wide Flood	HL Honeycomb louver
			NL No Lamp	
				5217 NOT for use in swimming pools or spas.



PROFESSIONAL OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.

LENS COVER CONSTRUCTION:

Injection-molded glass-reinforced polymer.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

OPTICS/AIMING:

Adjustable mounting bracket provides precise light aiming.
Adjustable lamp bracket provides up to $\pm 25^\circ$ of tilt. Lamp bracket can be locked into place to prevent disrupting lamp position when relamping.

MOUNTING:

Adjustable mounting bracket mounted on a cement counter weight base for stable placement underwater.

FASTENERS/INSERTS:

All fasteners are stainless steel with brass inserts.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.
Connectors for a required above-water connection are also included.

CAUTION:

Follow installation instructions as well as local electrical codes when installing.
NOT for use in swimming pools or spas.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°)
Narrow Spot **25** (25°)
Medium Flood **36** (36°)
Wide Flood **60** (60°)

DIMENSIONS

