| VISTA | MT Series Specification Sheet Commercial Series · Low Voltage · Transformer |
|-------|--|
| | Commercial Series \cdot Low Voltage \cdot Transformer |

| TYPE: | MODEL: |
|----------|--------|
| | |
| | |
| PROJECT: | |

PRODUCT FEATURES

| Wattage | 300 – 1200 W |
|----------------------|----------------------|
| Secondary Voltage | 11 – 15 VAC |
| Housing | Stainless Steel |
| Dimensions | 17″ H x 9″ W x 5½″ D |



EXAMPLE: MT-600DT

ORDERING INFORMATION

SERIES MODEL OPTIONAL FINISH

 MT

| SERIES MODEL | | OPTIONAL FINISH | | ORDERING NOTES | | | |
|--------------------------|-----------------------------|--|----|-----------------------------------|----------|---|---------------------------------|
| MT Multi-Tap Transformer | ap Transformer 300 | 300 Watts | | Clear powder coat finish standard | | See the following for accessory descriptions: | |
| | 300T | 300 Watts T timer * | В | Black | | | |
| | 300DT | 300 Watts DT timer * | z | Architectural Bronze | DT DA RP | T Removable multi-setting mechanical | |
| | 300DA | 300 Watts DA timer * | DZ | Dark Bronze | | 24-hour timer | |
| | 300RP | 300 Watts RP photocell * | GT | Granite | | Removable multi-setting digital | |
| | 600 | 600 Watts (300 W x 2) | w | White | | 7-day timer | |
| | 600T | 600 Watts (300 W x 2) \mid T timer * | BR | Architectural Brick | | | Removable multi-setting digital |
| | 600DT | 600 Watts (300 W x 2) \mid DT timer * | LZ | Light Bronze | | astronomical timer | |
| | 600DA | 600 Watts (300 W x 2) DA timer * | SB | Special Bronze | | Remote wired photocell with electronic timer | |
| | 600RP | 600 Watts (300 W x 2) RP photocell * | GG | Glossy Gray | | electronic timer | |
| | 900 900 Watts (300 V | 900 Watts (300 W x 3) | R | Rust | | Accessories not required for | |
| | 900T | 900 Watts (300 W x 3) \mid T timer * | HG | Hunter Green | | operation of transformer | |
| | 900DT | 900 Watts (300 W x 3) DT timer * | WB | Weathered Bronze | | | |
| | 900RP | 900 Watts (300 W x 3) \mid RP photocell * | wı | Weathered Iron | | | |
| | 1200 | 1200 Watts (300 W x 4) | GM | Graphite Metallic | | | |
| | 1200T | 1200 Watts (300 W x 4) \mid T timer * | G | Verde | | | |
| | 1200DT | 1200 Watts (300 W x 4) \mid DT timer * | P | Pewter | | | |
| | 1200RP | 1200 Watts (300 W x 4) RP photocell * | м | Mocha | | | |
| | | | OF | Olde Finish | | | |



SPECIFICATIONS

HOUSING CONSTRUCTION:

20-gauge 304 stainless steel.

 $\frac{1}{2}$ " - $\frac{3}{4}$ " knockouts on each side of enclosure for conduit and accessory mounting as well as a removable, swing-down enclosure bottom with Adjustable Cable Raceway Feeder and multiple $\frac{1}{2}$ " - $\frac{3}{4}$ " and 2" knockouts.

NEMA ENCLOSURE RATING:

3R

FINISH:

Clear powder coat finish standard. Also available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

TERMINALS:

- Low voltage terminal strip for multiple cable connections
- 120-volt terminal strip for easy hard-wiring and an accessory terminal strip

PRIMARY PROTECTION:

Auto thermal shut-off

SECONDARY PROTECTION:

Resettable high performance magnetic circuit breaker. Fully grounded and isolated with encapsulated core and coil.

WIRING

6-foot, heavy-gauge, grounded, water-resistant power cord with integrally molded plug.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

Pool & Spa Ready - Suitable for Use with Submersible Luminaires (power cord must be shortened to a 3-foot maximum length - see Installation Instructions).

AVAILABLE POWER RATING:

300, 600, 900 or 1200 Watts

PRIMARY VOLTAGE:


120 Volts


(Also available in 208V, 230V or 277V, 50 or 60 cycle - Special order only.)


SECONDARY VOLTAGE:

11, 12, 13, 14 and 15 Volts

DIMENSIONS









www.VistaPro.com \cdot email@vistapro.com \cdot Fax: (888) 670-VISTA (8478)