

TYPE:	MODEL:

## **PRODUCT FEATURES**

Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	4" DIA ×15%" H





# **ORDERING INFORMATION**

EXAMPLE: PR-2265-B-W-LB5ND

MOUNTING	MODEL	FINISH	LED	ORDERING NOTES
PR ABS Ground Stake	2265	B Black Z Architectural Bronze	<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp	Fixtures shipped with specified mounting hardware.
		DZ Dark Bronze GT Granite W White BR Architectural Brick	NL No Lamp  Custom length stems available - Consult local distributor.	
		LZ Light Bronze  SB Special Bronze  GG Glossy Gray		
		R Rust  HG Hunter Green  WB Weathered Bronze  WI Weathered Iron		
		GM Graphite Metallic G Verde P Pewter M Mocha OF Olde Finish		



## **SPECIFICATIONS**

## **HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

### **STEM CONSTRUCTION:**

½" schedule-40 aluminum pipe.

#### **FINISH**

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

#### I FNS:

Clear, high-impact polycarbonate lens.

### MOUNTING:

Bottom of stem threaded with ½" NPT.

# LED:

- Integrated LED Module. 2.5 5 Watts.
- G4 LED Lamp. 1.5 Watts.

### **ELECTRICAL:**

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

## **FASTENERS:**

All fasteners are stainless steel.

#### WIRING

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

#### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

# **DIMENSIONS**





